# iPulse M-1635 Safe Plus

Order no. 018638

## Equipment




- **Automatic impulse filter cleaning -** cleans the filters during suction operation - without air flow interruption for permanent operation!
- Demand-driven by pressure differential measurement!
- Cleaning of the filter cassettes with forces corresponding to 300 times the acceleration due to gravity (300 g) - perfectly suited for fine and problematic dusts (e.g. plaster)
- **High-performance turbine** with better suction power
- **Smartfix** - fixation of Systainer tool boxes. Innovative railings offer additional possibilities, e.g. the fixing of the suction hose with Velcro straps.
- **Push handle** for comfortable driving of the vacuum cleaner
- Power socket with automatic ON/OFF
- 2-stage speed regulation
- Air flow monitoring with acoustic warning signal / preselection switch for different hoseØ
- Filter indicator light
- Soft start control & tracking electronics
- Water level detection with sensor shutdown
- Antistatic preparation
- Carrying handle with fold-out cable hook
- Accessories optimally accommodated: 4 parking positions at the rear and 2 holders on the upper part
- Robust, double-walled container suitable for construction sites
- Large, reinforced wheels and castors, flush, stable locks
- **Rotary slide:** Easy handling - facilitates the flexible use of fleece and PE bags.
- **Container closure** for dust-free transport
- The scope of delivery includes the **QUIX** quick-change accessory system, which allows you to change accessories in no time at all—securely and conveniently.

**IFA-certified vacuum cleaner for slightly hazardous dusts of dust class M, dust retention capacity 99,9 %.**

**Dust-free and therefore healthier working!**

**More safety in the workplace!**

## Technical Data

| | |
|---|---|
| **Power consumption max.** | 1600 Watt |
| **Volume flow max.** | 75 l/s* |
| **Vacuum max.** | 280 mbar* |
| **Sound pressure level** | 69 dB(A) |
| **Container volume (max.) l Gross-dust-water** | 35 l; 25 l; 22 l; |
| **Dimensions (L x W x H) (incl. push handle)** | 66 cm x 40 cm x 92 cm |
| **Weight** | 16,8 kg |
| **Power cable length** | 8 m (Gummi, H07RN-F), rot |
| **Operating range** | 13,0 m |

* Measured at the motor head

## Scope of Supply

1x HANDLETUBE SOFTGRIP AS,QUIX
1x POWERTOOLADAPTER 28/35 AS,QUIX
1x POWERTOOLADAPTER 40/45 AS,QUIX
1x HOSE 35-500 AS black/red, QUIX
1x CREVICE NOZZLE
1x FLOORNOZZLE 30
2x SUCTION TUBE STAINLESSSTEEL




2 x FKP 4800 M Adv. filter (dust class M, ≥ 99.9%)
3 x FBPE 25/35 disposal bag

IP24 3 JAHRE GARANTIE



ELECTROSTAR GmbH ©