



ENGLISH

USER MANUAL

WWW.GOPOXY.CO



BRIEF GOPOXY INTRODUCTION



- ▶ **GoPoxy is a two-part epoxy grout** designed for a luxury and long lasting finish.
- ▶ **Built for heavy traffic** – Resists cracks and wear, even in busy areas.
- ▶ **Superior stain resistance** – Repels spills and dirt to keep floors pristine.
- ▶ **Long-lasting performance** – Maintains strength and colour over time.
- ▶ **Fully waterproof** – Perfect for wet area like bathrooms and wetrooms.
- ▶ **Low-maintenance care** – Stays clean without harsh chemicals.

ADVANTAGES

- | | |
|--------------------------------------|---------------------------------------|
| ✔ Floor and wall applications | ✔ Protects against discolouration |
| ✔ Cures to a solid non porous finish | ✔ Perfect for bathrooms and wet areas |
| ✔ Can be used for mitred edges | ✔ Hygienic |
| ✔ Anti Crack | ✔ Highly durable |
| ✔ Mold & mildew resistant | ✔ Simple application |

Before You Begin: *Helpful Prep Tips for a Perfect GoPoxy Finish*

Thanks for choosing GoPoxy! To get the best results, it's really important that your tiling area is fully dry and dust-free before you start grouting.

Unlike traditional grouts, GoPoxy is a two-part epoxy that doesn't react well to moisture. That means no sponges or water near the joints—keeping them completely dry will ensure strong bonding and a beautiful, even finish.

If you're prepping and grouting on the same day, please use dry methods only to clean the area. Let's walk you through how to prepare:

Step-by-Step Preparation Process

1. Make Sure Tiles & Adhesive Are Fully Set

Give the tile adhesive enough time to fully cure before grouting. Follow the adhesive manufacturer's guidelines, and avoid grouting while adhesive is still wet or soft.

2. Remove Tile Levelling Clips (if used)

Take out any levelling clips and check joints for leftover adhesive or ridges.

3. Clean the Grout Joints – Dry Only

Use a sharp utility knife to gently scrape out any adhesive from the joints. Aim for at least two-thirds of the tile depth, especially for repairs.

No water or sponges.

4. Vacuum the Joints

Use a vacuum to remove all the fine dust and debris—this helps the grout stick better.

Brushing alone might leave fine dust behind, so vacuuming is key!

5. Clean the Tile Faces (If Needed)

If you need to tidy up the tile surface itself, use a lightly damp, well-wrung microfiber cloth.

Be careful not to let any moisture drip into the joints.

What Not To Do

X Do not clean joints with water, buckets, or sponges.


X Do not grout over adhesive that is still curing or has entered the joint space.


X Do not assume that wiping the tile surface is enough—joints must be completely dry and adhesive-free.


INSTRUCTIONS


Always read the product instructions and safety information before use.


GoPoxy grout gun is required for application. This can be purchased from our stockists or from our website. GoPoxy finishing tools are also highly recommended.


- 


Prior to application, ensure all joints are clean, dry and free of any debris. Then apply GoPoxy Priming Wax to face of the tile along grout joints, making sure no wax gets into the joints.
- 

Remove cap of GoPoxy grout and attach the mixing nozzle. Attach the 'Guidance Tool' at this stage if you wish to use it.
- 

Place tube into the GoPoxy gun and squeeze handle to begin mixing the two components.
- 

Discard the first 30-40cm of GoPoxy to ensure the 2 components have mixed sufficiently.
- 

Once joints are clean, dry and free of any adhesive/debris, apply GoPoxy into the joints slowly to ensure joints are completely filled.
- 

Using one of the tools in the GoPoxy Tool Kit, run through several cross joints in one continuous pass, then work outward from each one to create a smooth, even cross section
- 

Leave to set for between 6 and 12 hours depending on temperature, then carefully remove excess from the face of the tile using the GoPoxy scraper supplied in the tool kit. Ensuring not to scrape or damage the face of the tile.

Please avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection. Wash hands thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.

SCOPE OF APPLICATION

Used for the filling of joints of various materials such as ceramic/porcelain tiles, glass, quartz etc.

ATTENTION

- During application if there's a break of more than 20 minutes, the epoxy in the mixing nozzle may solidify. If you find it difficult to apply or the grout cannot be dispensed, replace the mixing nozzle.
- GoPoxy Priming Wax should be used on the face of the tile along the grout joints. All natural stone must be fully sealed before application if applicable.
- For unused grout in the tube, remove the mixing nozzle, clean the top of the tube and put cap back on. The remaining grout can be used later with new mixing nozzle. GoPoxy 'POLY' Range cannot be reused one opened.
- Combustible liquid. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep cool. In case of fire: Use appropriate media to extinguish.
- Our company ensures the quality of the outgoing product. However, users should test the product suitability and application themselves. If there are issues due to improper application or external factors, we will not be held liable for any resulting damage or loss.
- If you need to remove the grout for any reason, apply heat using a heat gun to soften cured grout. Once soft, remove using suitable tools. Test an area to ensure that you do not damage the tiles or other materials. Avoid applying heat to the same area for extended periods of time. Always use suitable personal protective equipment.
- **Colour stickers are for reference only. Please refer to the GoPoxy 2-Part Epoxy Grout colour chart for accurate colour comparison.**

*Store in a cool, dry place between 8-18°C. Net content: e400ml. Use within 12 months of the date on neck of bottle. Dispose of contents/container in accordance with national regulation.
Keep GoPoxy and tools out of reach of children.*

Safety data sheet available on request.

COMMERCIAL INFORMATION: Portico Commerce Limited., 124 City Road, London, EC1V 2NX. Registered in United Kingdom SC776603.

DESIGNED IN THE UNITED KINGDOM. ASSEMBLED IN CHINA.

TOOL REQUIREMENTS

GoPoxy Toolkit is required for application.

COVERAGE

Need to work out how much GoPoxy is needed for your job? Coverage calculator available on www.GoPoxy.co.uk.

WARNING

Please avoid contact with skin and eyes.
Wear protective gloves/protective clothing/eye protection/face protection.
Wash hands thoroughly after handling.
IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.

Combustible liquid. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a well-ventilated place. Keep cool. In case of fire: Use appropriate media to extinguish.

Dispose of contents/container in accordance with national regulation.
Keep GoPoxy and tools out of reach of children.

Net Contents: e400ml.

Seal the deal.GoPoxy.



AFTERCARE

To keep your GoPoxy finish looking its best, clean regularly with a pH-neutral cleaner and a soft mop or cloth. Avoid acidic or alkaline cleaning products, as these can damage the grout's surface and reduce its lifespan. With gentle care, your grout will maintain its strength, colour, and stain resistance.

NO MESS EPOXY GROUT

- LARGE FLOORS
- COMMERCIAL SPACES
- BATHROOMS
- GYMS AND LEISURE CENTRES
- HOTELS AND HOSPITALITY

COMMERCIAL INFORMATION

Portico Commerce Limited., 124 City Road,
London, EC1V 2NX.

Registered in United Kingdom SC776603.

Designed in the United Kingdom.

Assembled in China.



WWW.GOPOXY.CO.UK